

Amendments to the Claims:

Please substitute the following clean copy text for the pending claims of the same number.

1. (Previously presented) A compression journal comprising:

at least two semi-circular segments;

a cylindrical shaft having said semi-circular segments positioned around said shaft;

at least one air gap positioned circumferentially between two of the semi-circular segments; and

means, positioned around the outside of said semi-circular segments, for maintaining electrical contact between said semi-circular segments and said cylindrical shaft.
2. (Previously presented) The compression journal as recited in claim 1 wherein said semi-circular segments comprise a silver impregnated graphite material.
3. (Previously presented) The compression journal as recited in claim 1 wherein said cylindrical shaft comprises a coin silver sleeve around an outer portion of said shaft for contacting said semi-circular segments.
4. (Original) The compression journal as recited in claim 1 wherein said journal comprises a shield for securing said journal within a stator assembly and blocking RF signal leakage.
5. (Previously presented) The compression journal as recited in claim 1 wherein said means for maintaining electrical contact between said semi-circular segments and said cylindrical shaft comprises a rubber O-ring.
6. (Previously presented) The compression journal as recited in claim 1 wherein said means for maintaining electrical contact between said semi-circular segments and said cylindrical shaft comprises a conductive O-ring.

7. (Original) The compression journal as recited in claim 1 wherein said compression journal is positioned within a rotary joint.

8. (Previously presented) A rotary joint comprising:
a rotor assembly having a housing and a shaft extending outward from a center portion thereof;

a stator assembly having a cylindrical opening for receiving said shaft of said rotor assembly, the housing of said rotor assembly being secured within a housing of said stator assembly;

a cavity in said stator assembly for receiving at least two semi-circular segments positioned around said shaft of said rotor assembly;

at least one air gap positioned circumferentially between the two semi-circular segments; and

means positioned around the outside of said semi-circular segments for maintaining electrical contact between said semi-circular segments and said shaft of said rotor assembly.

9. (Previously presented) The rotary joint as recited in claim 8 wherein said rotary joint comprises a shield, having an opening for said shaft to pass therethrough, positioned against an end of said semi-circular segments for securing said semi-circular segments within said cavity of said stator.

10. (Previously presented) The rotary joint as recited in claim 9 wherein said shield provides a ground connection between said semi-circular segments and said stator housing.

HAYES SOLOWAY P.C.
130 W. CUSHING ST.
TUCSON, AZ 85701
TEL. 520.882.7623
FAX. 520.882.7643

175 CANAL STREET
MANCHESTER, NH 03101
TEL. 603.668.1400
FAX. 603.668.8567

11. (Previously presented) The rotary joint as recited in claim 8 wherein said semi-circular segments comprise a silver impregnated graphite material.
12. (Previously presented) The rotary joint as recited in claim 8 wherein said cylindrical shaft comprises a coin silver outer sleeve for contacting said semi-circular segments.
13. (Previously presented) The rotary joint as recited in claim 8 wherein said means for maintaining electrical contact between said semi-circular segments and said shaft comprises a rubber O-ring.
14. (Previously presented) The rotary joint as recited in claim 8 wherein said means for maintaining electrical contact between said semi-circular segments and said shaft comprises a conductive O-ring.
15. (Previously presented) The rotary joint as recited in claim 8 wherein said cavity of said stator assembly comprises a channel having a predetermined width within said cavity for receiving said means for maintaining electrical contact between said semi-circular segments and said shaft.
16. (Original) The rotary joint as recited in claim 8 wherein said housing of said rotor assembly comprises a bearing ring positioned around an outer end portion of said housing to facilitate rotation of said rotor assembly when positioned within said stator assembly.
17. (Original) The rotary joint as recited in claim 8 wherein said rotor assembly

HAYES SOLOWAY P.C.
130 W. CUSHING ST.
TUCSON, AZ 85701
TEL. 520.882.7623
FAX. 520.882.7643

175 CANAL STREET
MANCHESTER, NH 03101
TEL. 603.668.1400
FAX. 603.668.8567

comprises a first capacitive feed ring through which said shaft extends and said stator assembly comprises a second capacitive feed ring through which said shaft passes, said first capacitive feed ring being disposed in close relationship to said second capacitive feed ring when said rotor assembly is positioned within said stator assembly.

18-23 (Cancelled)

24. (New) A compression journal comprising:

at least two semi-circular segments;

a cylindrical shaft having said semi-circular segments positioned around said shaft;

a conductive sleeve bonded to the shaft;

at least one air gap positioned circumferentially between two of the semi-circular segments; and

means, positioned around the outside of said semi-circular segments, for maintaining electrical contact and physical contact between said semi-circular segments and said conductive sleeve.

25. (New) The compression journal as recited in claim 1 wherein said semi-circular segments are in constant electrical contact with said shaft.

HAYES SOLOWAY P.C.
130 W. CUSHING ST.
TUCSON, AZ 85701
TEL. 520.882.7623
FAX. 520.882.7643

175 CANAL STREET
MANCHESTER, NH 03101
TEL. 603.668.1400
FAX. 603.668.8567